

MAGEWELL

Pro Convert HDMI Plus Module Technical Specifications

Copyright (c) 2011–2024 [Nanjing Magewell Electronics Co., Ltd.](#) All rights reserved.

Specifications are based on current hardware, firmware and software revisions, and are subject to change without notice.

HDMI, the HDMI logo and High-Definition Multimedia interface are trademarks or registered trademarks of HDMI Licensing LLC. NDI[®] is trademark or registered trademark of Vizrt Group.

Revised on 15/03/2024

Interfaces

- 1* RJ45 1000Mbps Ethernet port
- 1* USB Type-C port for configuration
- 1* HDMI 1.4 input port
- 1* HDMI 1.4 output port
- 1* Modator interface for connecting to Modator 2U (hot-swappable)

Input & Loop Through Features

- Max. input & loop through signal:
 - 4096x2160 30fps 4:4:4/4:2:2
 - 4096x2160 60fps 4:2:0
- Input videos at any format by customizing the EDID of input port
- Supports RGB and YUV BT.601/709 signals
- Supports 8-channel HDMI-embedded audio

NDI[®] Encoding Features

- Encode and output real-time streams of Full NDI[®] at up to 2048x2160 120fps 4:2:2 8-bit
- Output the same resolution as input or any custom resolution. Typical outputs include:
 - 2048x1080p/1920x1080p 23.98/24/25/29.97/30/50/59.94/60
 - 1280x720p 23.98/24/25/29.97/30/50/59.94/60/100/119.88/120
 - 1920x1080i 25/29.97/30/50/59.94/60
 - 720x480p/720x480i 59.94/60/119.88/120
 - 720x576p/720x576i 50/100
- Output frame rate same as the original, 1/2, 1/3 or 1/4 of input frame rate
- Encode 8-channel NDI-embedded audio
- Supports NDI[®] 6.0

Web UI

- Register with Magewell Control Hub for remote centralized management
- Supports configuring and managing via Web UI
- Provides comprehensive information regarding the device and signals in real-time
- Allow to configure how a signal is encoded and output, including deinterlacing, EDID settings, up/down scale, frame rate, aspect ratio, as well as the network connection
- Supports updating firmware
- Supports USB RNDIS/ECM
- Supports IE/Edge/Firefox/Chrome/Safari/Opera web browsers
- Provides HTTP APIs

LED Indicators

- Input signal:
 - On: locked
 - Off: unlocked
- Loop through signal:
 - On: device connected and signal detected
 - Off: undetected

Physical Specifications

- Form factor: 184.4mm (L) x 30.0mm (W) x 81.5mm (H)
- Weight: ≈295g

Power Consumption

- Max power consumption: 6.2W

Working Environment

- Operating temperature: -10 to 45 deg C
- Storage temperature: -20 to 70 deg C
- Relative humidity: 5% to 90% non-condensing